



Band it Pok it Tool

Pok-It II Tool J020 is a lightweight pocket sized tool for use with 3M AC Series Kit. Applies tension and includes built-in cutter. Weight 1.1lbs (.5kg).



3M™ Constant Force Springs

Scotchcast™ Constant Force Springs are a range of solderless connections for use on lead or aluminium sheaths and copper screened cables.

The springs are easily applied by rolling onto the sheath connections, whereupon it continues to exert a constant pressure.

PART NUMBER	INNER DIAMETER OF SPRING	SPRING WIDTH	SPRING TAPE LENGTH (Mm)	MIN DIA	MAX DIA
P59	3.5	9	80	4	10
P60	7.5	10	175	9	15
P61	11	16	225	14	22
P62	14.5	16	295	18.5	29
P63	18.5	16	375	23.5	37
P64	25	16	505	31	50
P65	32	20	710	44	70
P66	44	20	935	58	94
P67	57	20	1250	70	110



3M™ Earth Bonding Kits SB 1 - SB4

Scotchcast™ Spring Bonding Kits may be used to bond the armour wires on armoured cables in 'Scotchcast' Cable jointing, including the 'resin pressure method' of jointing. The SB kits provide an electrical bond and should be used where earthing leakage protection is installed.

The SB Series contains two constant force springs; copper braid and insulating tape and can be applied without the aid of special tools.

KIT	ACCEPTED CABLE DIAMETER (Mm)		LENGTH OF COPPER CORD	
	MAX	MIN	MIN	MIN
SB1	12	9	200	250
SB2	19	14	320	350
SB3	25	23.5	350	400
SB4	38	31	400	450