

DESCRIPTION:

This high-grade PVC sleeving has a thin wall that makes it ideal for insulating wire in areas where space is premium. Supplied in continuous 100m coils. Some sizes are available supplied on reels, please contact us for more information.

APPLICATIONS:

Ideal for insulating wire in areas where space is at a premium.

SPECIFICATION:

MATERIAL: PVC
OPERATING TEMPERATURE: -20°C to +70°C
COLOUR: Green/Yellow
INSULATION RESISTANCE: 1010 Ohm/cm
DIELECTRIC STRENGTH: 20 kV/mm
ELONGATION AT BREAK: 220%
HARDNESS: BSS20-30
FLAMMABILITY: Self-Extinguishing in 30 seconds.
SPECIFICATION: BS 2848/3/85T, RoHS compliant

PART NUMBERS:

PART NUMBER	INTERNAL DIA. (mm)	TO COVER CABLE SIZE (mm ²)	COIL LENGTH (m)
GREEN/YELLOW PVC SLEEVING COILS			
CY 1.5 GREEN/YELLOW	1.5	-	100
CY 2.0 GREEN/YELLOW	2.0	-	100
CY 3.0 GREEN/YELLOW	3.0	0.5-0.75	100
CY 4.0 GREEN/YELLOW	4.0	1.5-2.5	100
CY 5.0 GREEN/YELLOW	5.0	2.5-4.0	100
CY 6.0 GREEN/YELLOW	6.0	6.0	100
CY 8.0 GREEN/YELLOW	8.0	10.0	100
CY 10.0 GREEN/YELLOW	10.0	16.0-25.0	100
CY 12.0 GREEN/YELLOW	12.0	35.0	100
CY 15.0 GREEN/YELLOW	15.0	50.0	100

Also available in 105T grade and UL approved versions. Sizes up to 40mm can be produced, minimum order quantities apply. Please contact us for more information.



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297